

Product Data Sheet



Product	SP203 Acrylic Drywall Basecoat.
Description/Uses	SP203 is an acrylic-based primer sealer, specifically designed for SPII waterbased finishes. It should be used over new or previously painted drywall, plaster and smooth masonry surfaces. SP203 provides excellent enamel holdout, adhesion, and alkali resistance. For water soluble stains, seal with SP222 ECO-BLOCK™ prior to general priming with SP203.
Surface Preparation	Standard painting practices and procedures which are followed normally in the painting profession should be used to clean and prepare surfaces before painting. All surfaces must be clean, dry, free of dust, grease or other contaminants. New plaster: All plaster surfaces must be thoroughly dry and cured at least 30 days. Previously painted surfaces: Sand or otherwise de-gloss higher sheen surfaces.
DOT Class	Not regulated.

Application Information	
Method	Brush, roll or spray.
Drying Time	30-60 minutes to touch; recoat in 1-2 hours at @ 70° F and 50% RH.
Thinning	If necessary for spray, add up to one pint per gallon.
Tinting	Not recommended.
Clean Up	Warm soapy water.
HMIS	Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: E.
Environmental	Consult with local regulatory and governmental agencies for VOC compliance and disposal methods.

Specifications	
Color	White.
Solids by Volume	34.0%.
Weight per Gallon	11.62 lbs.
Gloss	Flat (@ 60° angle).
Coverage	250-350 sq ft/gal depending on surface porosity, texture and method of application.
Shelf Life	Minimum one year.
Maximum VOCs	66 grams/liter or 0.55 lbs/gal.
CAUTION	Protect from freezing. Do not apply when temperature of paint or surface is below 50° F or relative humidity is above 75%.