

Product Data Sheet



Product	SP97 Multi-Purpose Waterbase Basecoat.
Description/Uses	SP97 is a fast drying, waterbased, multi-purpose primer specifically designed for use in conjunction with all SPII specialty finishes. It has been formulated with an acrylic resin to provide excellent adhesion over a variety of interior surfaces like plastic, glass, ceramic tile, glazed block and other high density materials. Also used as a barrier coat over vinyl wallcovering.
Surface Preparation	Standard painting practices and procedures which are followed normally in the painting profession should be used to clean and prepare surfaces before painting. NOTE: For use on wood, check a small section before proceeding. Application may show grain raising.
DOT Class	Not regulated.

Application Information	
Method	Spray preferred. Brush or roll small areas only.
Drying Time	30 minutes to touch; 30-45 minutes to recoat at @ 70° F and 50% RH. Topcoat within 48 hours.
Thinning	Not required. Reduce with water, if necessary. Over-thinning may result in loss of hide and retard drying.
Tinting	Not recommended.
Clean Up	Warm soapy water while coating is wet. After drying, use lacquer thinner. CAUTION: Do not allow to dry in equipment.
HMIS	Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: H.
Environmental	Consult with local regulatory and governmental agencies for VOC compliance and disposal methods.

Specifications	
Color	White.
Solids by Volume	47.0%.
Weight per Gallon	10.60-10.80 lbs.
Gloss	Flat (@ 60° angle).
Coverage	300-400 sq ft/gal depending on surface porosity, texture and method of application.
Shelf Life	Minimum one year.
Maximum VOCs	200 grams/liter or 1.67 lbs/gal.
CAUTION	Protect from freezing. Do not apply when temperature of paint or surface is below 50° F or relative humidity is above 75%.