

SP1000 Clear Coat

PRODUCT DATA SHEET



FINISH DESCRIPTION

SP1000 is a waterbased acrylic clear coat that provides an exceptional abrasion and crack-resistant protective clear coating for Zolatone finishes. The dry film is crystal clear and non-yellowing. When fully cured, SP1000 exhibits great resistance to chemicals, and is very cleanable. The product is available in a flat, satin or gloss sheen and offers excellent gloss retention.

FEATURES

BENEFITS

Crystal Clear Finish

Non-yellowing and durable

Easy Application

Any quality painting contractor can apply

Waterbased / Low VOC

112 g/L -- Low odor spray application and can be applied in occupied spaces

Warranty

5 – Year manufacturer’s warranty against adhesion failure if product is correctly applied

Class A fire rated

Like all Zolatone finishes, SP1000 is Class A fire rated.

RECOMMENDED USES

SP1000 is a protective clear coat used to enhance durability, cleanability and the aesthetic of any Zolatone finish. SP1000 may also be used to alter the sheen of ordinary paint finishes like Flex Pure Color and is available in Flat, Satin or Gloss.

Application:

Applied by professional painting contractors.
May be sprayed HVLP or by Conventional Air Spray equipment. Refer to printed application instructions for steps and all equipment set up.

Call your Zolatone distributor or MCT for details 1-800-765-6699.

TECHNICAL INFORMATION

System Components	Waterbased Acrylic Urethane Clear Coat	
Finish Appearance	Smooth finish. Crystal clear finish with Flat, Satin or Gloss sheen	
Application	Commercial painting contractors. May be sprayed HVLP or by conventional air spray. Call your Zolatone distributor or MCT for details 1-800-765-6699.	
Coverage Rates	300-400 sq. ft. per gallon	
Maximum VOC	< 112 g/L	
Fire Rating	Clear Coat - Class A or I	ASTM E-84-91a

FIVE YEAR LIMITED WARRANTY

Master Coating Technologies warrants the Zolatone components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's current printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. Master Coating Technologies shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product.

SAFETY INFORMATION

Some persons may experience an allergic reaction to paint products if exposed to spray mist. Because spray application of this Zolatone finish may create a fine mist of product and product catalyst in the immediate application area, a high-efficiency particulate respirator and protective glasses or goggles should be worn by the applicator. The immediate application area should be "cautioned-off" to prevent persons without safety equipment from coming into contact with mist. Ensure good ventilation. Product SDS sheets are available from MCT by calling 1-800-765-6699.

First Aid: Ingestion – induce vomiting, consult a physician. Skin contact – wash with soap and water. Eye contact – immediately flush eyes for 15 minutes occasionally lifting eyelids. If contact lenses are worn, remove lenses and continue rinsing. Clean lenses before reusing - may not be possible to reuse. Obtain medical attention. Refer to product SDS. In case of emergency, call 1-800-765-6699



Zolatone Interior Finishes
2777 Eagandale Boulevard
Eagan, MN 55121
www.Zolatone.com
800.765.6699